FINAL REPORT JULY 1997 19980914 017

REPORT NO. 97-04

2.75-INCH, HYDRA 70, PA150, ROCKET PALLET FIRST ARTICLE TESTING (FAT)

Prepared for:

U.S. Army Armament Research, Development and Engineering Center
ATTN: AMSTA-AR-ESK
Rock Island, IL 61299-7300

Distribution Unlimited



SAVANNA, ILLINOIS

VALIDATION ENGINEERING DIVISION SAVANNA, ILLINOIS 61074-9639

AVAILABILITY NOTICE

A copy of this report will be furnished each attendee on automatic distribution. Additional copies or authority for reprinting may be obtained by written request from Director, U.S. Army Defense Ammunition Center, ATTN: SIOAC-DEV, 3700 Army Depot Road, Savanna, IL 61074-9639.

DISTRIBUTION INSTRUCTIONS

Destroy this report when no longer needed. Do not return.

Citation of trade names in this report does not constitute an official endorsement.

The information contained herein will not be used for advertising purposes.

UNCLASSIFIED SECURITY CLASSIFICATION OF THIS PAGE

	REPORT DO	CUMENTATIO	N PAGE				Approved 3 No. 0704-0188
1a. REPORT SECURITY CLA	ASSIFICATION		1b. RESTRICTIV	E MARKINGS			
UNCLASSIFIEI)						
2a. SECURITY CLASSIFICAT			3. DISTRIBUTIO	N / AVAILABILITY O	F REPORT		
2b. DECLASSIFICATION / DO	OWNGRADING SCHEDULE			MITED			
			UT VE				
4. PERFORMING ORGANIZA	ATION REPORT NUMBER(S	5)	5. MONITORING	ORGANIZATION RI	EPORT NUI	MBER(S)	
07.04							
97-04							
6a. NAME OF PERFORMING U.S. Army Defei		6b. OFFICE SYMBOL (if applicable)	7a. NAME OF MO	DNITORING ORGAN	IZATION		
Ammunition Cer		SIOAC-DEV					
6c. ADDRESS (City, State, ar		SIOAC-DEV	7b. ADDRESS (C	ity, State, and ZIP C	ode)		
ATTN: SIOAC-	DEV				ŕ		
Savanna, IL 610							
8a. NAME OF FUNDING / SP ORGANIZATION	ONSORING	8b. OFFICE SYMBOL (if applicable)	9. PROCUREME	NT INSTRUMENT ID	ENTIFICAT	TION NUM	IBER
U.S. Army Arma	ment Research.	(ii applicable)					
1	l Engineering Cente	AMSTA-AR-E	\$K				
8c. ADDRESS (City, State, ar			10. SOURCE OF	FUNDING NUMBER	ks .		
ATTN: AMSTA	_AR_FSK		PROGRAM ELEMENT NO.	PROJECT NO.	TASK NO).	WORK UNIT ACCESSION NO.
Rock Island, IL			ELEGIZITI NO.				ACCESSION NO.
11. TITLE (Include Security C			L	<u> </u>			
		CD-11-4 Dina A41-1		· T D\			
2.73-Inch, Hydra	70, PA150, Rocket	Pallet First Artic	le l'esting (FA	(1)			
12. PERSONAL AUTHOR(S)							
Quinn D. Hartma	an						
13a. TYPE OF REPORT	13b. TIME COVE	RED	1	PORT (Year, Month,	Day)	15. PAGE	COUNT
Final	FROM	то	1997	July		<u> </u>	
16. SUPPLEMENTARY NOTA	ATION						
47 COSATI O	ODEC	40 OUD FOT TERMS	10				
17. COSATI C		18. SUBJECT TERMS	(Continue on revers	e If necessary and id	lentify by ble	ock numbe	er)
40. 45075407 (0. #		177 1 11 1 1 1					
19. ABSTRACT (Continue on		• •		-		(876	
u	rmy Defense Ammi				-	•	, .
R -	e U.S. Army Armar		-			•	,
H.	cle MIL-STD-1660	_			_		•
k -	0, rocket pallet pro	•					
11	testing indicated that	at the pallet, adapt	ers, and conta	iners produced	l by Del	fasco n	net
MIL-STD-1660	test requirements.						
							
20. DISTRIBUTION / AVAILA				SECURITY CLASSIF	ICATION		
	SAME AS RPT.DTIC USER	s		ASSIFIED			Commence & According
22a. NAME OF RESPONSIBI				E (Include Area Code	9)		ICE SYMBOL
JEROME H. KR	UHN		815-273	3-8929		SIO	AC-DEV

U.S. ARMY DEFENSE AMMUNITION CENTER VALIDATION ENGINEERING DIVISION SAVANNA, IL 61074-9639

REPORT NO. 97-04

2.75-INCH, HYDRA 70, PA150, ROCKET PALLET FIRST ARTICLE TESTING (FAT)

TABLE OF CONTENTS

PART	PAGE NO.
1. INTRODUCTION	1-1
A. BACKGROUND	1-1
B. AUTHORITY	1-1
C. OBJECTIVE	1-1
D. CONCLUSION	1-1
2. ATTENDEES	2-1
3. TEST PROCEDURES	3-1
4. TEST EQUIPMENT	4-1
5. TEST RESULTS	5-1
6. PHOTOGRAPHS	6-1
7. DRAWINGS	7-1

INTRODUCTION

- A. BACKGROUND. The U.S. Army Defense Ammunition Center (DAC), Validation Engineering Division (SIOAC-DEV), was tasked by the U.S. Army Armament Research, Development and Engineering Center (ARDEC) to conduct first article MIL-STD-1660, Design Criteria for Ammunition Unit Loads, testing on the 2.75-inch, Hydra 70, PA150, rocket pallet produced by Delfasco of Tennessee, Greeneville, TN.
- B. AUTHORITY. This test was conducted IAW mission responsibilities delegated by the U.S. Army Armament, Munitions and Chemical Command (AMCCOM), Rock Island, IL. Reference is made to the following:
- 1. Change 4, 4 October 1974, to AR740-1, 23 April 1973, Storage and Supply Activity Operation.
 - 2. AMCCOM-R, 10-17, Mission and Major Functions of USADACS, 13 January 1986.
- C. OBJECTIVE. The objective of the tests was to determine if the pallets produced by Delfasco met MIL-STD-1660 test requirements prior to the acceptance of the pallets by the U.S. Army (USA).
- D. CONCLUSION. Two of the three pallets submitted by Delfasco were evaluated using MIL-STD-1660 test requirements. No significant flaws were found in the two pallets during testing so the third pallet was not evaluated. As a result of the performance of the pallets during testing, the 2.75-inch, Hydra 70, PA150, rocket pallet produced by Delfasco is recommended for USA-wide use.

MARCH - AUGUST 1996

ATTENDEES

Quinn D. Hartman

General Engineer

DSN 585-8992

815-273-8992

Jerry H. Krohn

Supervisory General Engineer

DSN 585-8908

815-273-8908

Thomas J. Michels

Supervisory General Engineer

DSN 585-8080

815-273-8080

Mark Rehmstedt

Packaging Engineer

DSN 493-8206

309-782-8206

Director

U.S. Army Defense Ammunition Center

ATTN: SIOAC-DEV

3700 Army Depot Road

Savanna, IL 61074-9639

Director

U.S. Army Defense Ammunition Center

ATTN: SIOAC-DEV

3700 Army Depot Road

Savanna, IL 61074-9639

Director

U.S. Army Defense Ammunition Center

ATTN: SIOAC-DES

3700 Army Depot Road

Savanna, IL 61074-9639

U.S. Army Armament Research, Development

and Engineering Center

ATTN: AMSTA-AR-ESK

Rock Island, IL 61299-7300

TEST PROCEDURES

The test procedures outlined in this section were extracted from MIL-STD-1660, Design Criteria for Ammunition Unit Loads, 8 April 1977. This standard identifies nine steps that a unitized load must undergo if it is to be considered acceptable. The four tests that were conducted on the test pallets are summarized below.

A. STACKING TEST. The unit load was loaded to simulate a stack of identical unit loads stacked 16 feet high, for a period of one hour. This stacking load was simulated by subjecting the unit load to a compression weight equal to an equivalent 16-foot stacking height. The compression load was calculated in the following manner. The unit load weight was divided by the unit load height in inches and multiplied by 192. The resulting number was the equivalent compressive force of a 16-foot-high load.

B. REPETITIVE SHOCK TEST. The repetitive shock test was conducted IAW Method 5019, Federal Standard 101. The test procedure is as follows: The test specimen was placed on, but not fastened to, the platform. With the specimen in one position, the platform was vibrated at 1/2-inch amplitude (1-inch double amplitude) starting at a frequency of approximately 3 cycles per second. The frequency was steadily increased until the package left the platform. The resonant frequency was achieved when a 1/16-inch-thick feeler gage momentarily slid freely between every point on the specimen in contact with the platform at some instance during the cycle or a platform acceleration achieved 1 +/- 0.1 Gs. Midway into the testing period, the specimen was rotated 90 degrees and the test continued for the duration. Unless failure occurred, the total time of vibration was two hours if the specimen was tested in one position and three hours for more than one position.

C. EDGEWISE ROTATIONAL DROP TEST. This test was conducted using the procedures of Method 5008, Federal Standard 101. The procedure for the edgewise rotational drop test is as follows: The specimen was placed on its skids with one end of the pallet supported on a beam 4-1/2 inches high. The height of the beam was increased if necessary to ensure that there was no support for the skids between the ends of the pallet when dropping took place, but was not high enough to cause the pallet to slide on the supports when the dropped end was raised for the drops. The unsupported end of the pallet was then raised and allowed to fall freely to the concrete, pavement, or similar underlying surface from a prescribed height. Unless otherwise specified, the height of drop for level A protection conforms to the following tabulation:

	DIMENSIONS OF		
GROSS WEIGHT	ANY EDGE, HEIGHT	HEIGHT C	OF DROPS
(WITHIN RANGE	OR WIDTH (WITHIN	ON E	DGES
LIMITS)	RANGE LIMITS)	Level A	Level B
(Pounds)	(Inches)	(Inches)	(Inches)
150 - 250	60 - 66	36	27
250 - 400	66 - 72	32	24
400 - 600	72 - 80	28	21
600 - 1,000	80 - 95	24	18
1,000 - 1,500	95 - 114	20	16
1,500 - 2,000	114 - 144	17	14
2,000 - 3,000	Above 145 - No limit	15	12
Above - 3,000		12	9

D. INCLINE-IMPACT TEST. This test was conducted by using the procedure of Method 5023, Incline-Impact Test of Federal Standard 101. The procedure for the incline-impact test is as follows: The specimen was placed on the carriage with the surface or edge to be impacted

projecting at least 2 inches beyond the front end of the carriage. The carriage was brought to a predetermined position on the incline and released. If it was desired to concentrate the impact on any particular position on the container, a 4- by 4-inch timber was attached to the bumper in the desired position before the test. No part of the timber was struck by the carriage. The position of the container on the carriage and the sequence in which surfaces and edges were subjected to impacts was at the option of the testing activity and depends upon the objective of the tests. This test was to determine satisfactory requirements for a container or pack, and, unless otherwise specified, the specimen was subjected to one impact on each surface that has each dimension less than 9.5 feet. Unless otherwise specified, the velocity at time of impact was 7 feet per second.

TEST EQUIPMENT

A. Compression Tester.

1. Manufacturer: Ormond Manufacturing

2. Platform: 60- by 60-inches

3. Compression Limit: 50,000 pounds

4. Tension Limit: 50,000 pounds

B. Transportation Simulator.

1. Manufacturer: Gaynes Laboratory

2. Capacity: 6,000-pound pallet

3. Displacement: 1/2-inch amplitude

4. Speed: 50 to 400 rpm

5. Platform: 5- by 8-foot

C. Inclined Plane.

1. Manufacturer: Conbur Incline

2. Type: Impact Tester

3. Grade: 10 percent incline

4. Length: 12-foot

TEST RESULTS

Two of three pallets submitted by Delfasco of Tennessee were inertly loaded to the specified design weight using two 4- by 4-inch lengths of lumber, two 2- by 4-inch lengths of lumber, and a quantity of ammunition simulant to bring each container individually to the required weight. Special care was taken to ensure that each container had the proper amount of weight in order to achieve a realistic pallet center of gravity (CG). Once properly prepared, the first two pallets were tested using MIL-STD-1660, Design Criteria for Ammunition Unit Loads, requirements. As a result of the good performance of the pallets during testing, the third pallet submission was not tested.

A. PALLET NO. 1.

Date:

19 November 1996

Weight:

2,245 pounds

Length:

78-1/2 inches

Width:

29-3/8 inches

Height:

43-1/2 inches

- 1. Compression Test. The test pallet was compressed with a load force of 9,900 pounds for 60 minutes. No damage was noted as a result of this test.
- 2. Repetitive Shock Test. The test pallet was vibrated 90 minutes at 220 RPM in the longitudinal orientation and 90 minutes at 185 RPM in the lateral orientation. Small cracks were noted to have formed in the pallet posts next to the pallet skids at the completion of the longitudinal vibration test. No change in the cracks was noted after the lateral vibration.

3. Edgewise Rotational Drop Test. The test pallet was edgewise rotationally dropped from a height of 15-inches on the longitudinal and lateral drops. No additional cracking was noted in the pallet posts.

4. Sling Compatibility Test. The test pallet was lifted off of the ground using the toplift adapter by four points, three points, two diagonal points, two adjacent points, and one point. No shifting of the containers or permanent deformation of the toplift adapter was noted.

5. Incline-Impact Test. The test pallet was incline-impacted on all four sides from a height of 8 feet. No additional damage was noted at the completion of the test.

6. Post Test Inspection. Following completion of MIL-STD-1660 testing, the pallet was disassembled and inspected for additional damage. The cracks noted at the completion of the longitudinal vibration test had not increased significantly. No significant damage was noted in the top or bottom adapters or the pallet deck.

B. PALLET NO. 2.

Date:

20 November 1996

Weight:

2,245 pounds

Length:

78-1/2 inches

Width:

29-3/8 inches

Height:

43-1/2 inches


1. Compression Test. The test pallet was compressed with a load force of 9,900 pounds for 60 minutes. No damage was noted as a result of this test.

2. Repetitive Shock Test. The test pallet was vibrated 90 minutes at 220 rpm in the longitudinal orientation and 90 minutes at 155 rpm in the lateral orientation. Three small cracks were noted to have formed in the pallet posts next to the pallet skids at the completion of the longitudinal vibration test. Following completion of the lateral vibration, the cracks were noted

to have increased in size and extended from the edge of the skid up to the strengthening dimple in the pallet post.


- 3. Edgewise Rotational Drop Test. The test pallet was edgewise rotationally dropped from a height of 15 inches on the longitudinal and lateral drops. No additional cracking was noted in the pallet posts.
- 4. Sling Compatibility Test. The test pallet was lifted off of the ground using the toplift adapter by four points, three points, two diagonal points, two adjacent points, and one point. No shifting of the containers or permanent deformation of the toplift adapter was noted.
- 5. Incline-Impact Test. The test pallet was incline-impacted on all four sides from a height of 8 feet. No additional damage was noted at the completion of the test.
- 6. Post Test Inspection. Following completion of MIL-STD-1660 testing, the pallet was disassembled and inspected for additional damage. The cracks noted at the completion of the vibration test had not increased significantly. No significant damage was noted in the top or bottom adapters and only minor deformation was noted on the pallet deck.

PHOTOGRAPHS



U.S. ARMY DEFENSE AMMUNITION CENTER AND SCHOOL -	SAVANNA, IL
MUNITION	SAVANNA, IL

PHOTO NO. A0317-SCN-97-1159. This photograph shows the side view of one of the three pallets submitted by Delfasco of Tennessee.




U.S. ARMY DEFENSE AMMUNITION CENTER AND SCHOOL - SAVANNA, IL

PHOTO NO. A0317-SCN-97-1163. This photograph shows the end view of one of the three pallets submitted by Delfasco of Tennessee.

DRAWINGS

_		FEVISION		
_	1.0	NO STATE OF THE COM	ONTE	ONOHA.
	•	PRODUCT BASE, INE		
		EFR M4R2001 94-03-25	94-03-25 SCHULTZ	SCHULTZ
	٧	NOR MST3003 95-06-22	11-10-96	
		(ECP MBR3004) 96-02-22		



COMBINATION OF ADOPTED LIEMS	PART NO
PALLET - SPECTAL STZE 78,50 X 29,31 SPEET HETAL	ACV00165
TOP ASSEMBLY - PALLET ADAPTER PAISO CONTAINER	ACV00159
BOTTOH ASSEMBLY - PALLET ADAPTER PAISO CONTAINER	ACV00160
UNITIZATION DRAWING	19-48-4231/61- 20PH1006

DISTRIBUTION IS UNLIMITED.

DISTRIBUTION STATEMENT A. APPROVED FOR PUBLIC RELEASE;	
S & &	
APPROVED FOR PUBLIC RE	

COMBINATION OF ADDRESS.

PALLET AND PALLET ADAPTER.

IN INITIALITION OF PALSO CONTAINER

B 28620 ACVOUSS

EACH OF LINE OF THE CONTAINER


EACH OF THE CONTAINER


EXT ASSY USED ON APPLICATION


MAYORI MAITION AND CHEEK DOWN DESIS WALNITON COMEN NO SCOR. EXVINENT BLEDGE 61074-625


9.4-03-25 B.K SYS SCHLLTZ


MALES OVERHIE HOUSE ENDECTION AND IN HOUSE SAME OFFICE AND ENDECTION FALCIDE BY PACE OFFI BY PAC











94-03-25 SCHULTZ 96-04-11 DATE APPROVE (EXION ACTIVITY

U.S. AND CONTENT CONVEY

DEPTH AND CONVEY

EXISTENCY CONVEY


EXISTENCY CONVEY

EXISTENCY CONVEY


EXISTENCY CONVEY

EXISTENCY

EXISTENCY ACV00163 SOUARE BELL. Restraint PART NO ACVOOLES - PRODUCT BASELINE EFF MA2001 94-03-25 A NOF H513003 95-06-22 (ECP NF13004) 96-02-22 SCALE 1/2 UNIT WE 11.2 CAR COOR | 1 2.8620 WILLIAM F. EPNST - 0.25 1.06 MALESS OFFER IS, NOTED SEAR STATES OF THE POSTS. SPEAK STATES OF THE POSTS. SPEAK STATES OF THE POSTS. SPEAK STATES OF THE POSTS OF THE 10 GA (.13) 4.63 APPLICATION L 0.25 4 PLACES 29.10 NOTES:
1. BOD RADII 0.13 INCH NAX WEEF NOT NOTED.
2. ANST Y14. SH-1982, NIL-A-2550 AND NIL-A 70798 APPLY.
3. NATERIAL: SHEET, SAC OR ANST 1005-1010 STEEL,
CARBON, COLD ROLL OR HOT ROLL,
PER ASTM A569, (ASTM A366 OR A569). - 2 PLACES 2 PLACES ∠ 0.25 x 451 1° 2 PLACES APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED. DISTRIBUTION STATEMENT A. 0.75+13 2.31 +.13



94-03-25 SCHALTZ 06-04-11]SÆFF (OF | DATE | APPR MATERIAL US. APP.
MATERIAL COSAND
DESCRIPTION OF CONTRACT COSAND
DESCRIPTION OF CONTRACT COSAND
EAVISED. ILL BIOIT 61074-9639 ACV00167 DECK-PALLET SPECTAL SIZE 78.50 X 29.31, SHEET METAL PART NO ACVOOLG7 - PRODICT BASE INE BTR MRZ001 94-03-25 A NOR PST3003 95-06-22 0.44 +.13 4 HOLES ⊕ 0.06 ⊕ A 28620 1.50 x 457 H 3.66 1.13 4 PLACES B.K. SYS SCHUTZ
JS J.K. T. J. NICHELS 2.75 8 PLACES P.F. EPNST WILLIAM F. EPNST 94-03-25 WALES ONCHRESS FOR STATE OF ST SOME HIDDEN LINES ONITIED FOR CLARITY 51.00 ACVOOLES 2.75 HYDRA ROCKET NEXT ASSY USED ON APPLICATION - 78.50^{4.25} -2.75 -26 PLACES 13.75 Ŧ 3.50+13 28.31 0.501 29.31 1.25 -¥-0.50 NOTES:
1. ACT FAULT O. 13 INCH MAX WERE NOT NOTED.
2. ACT VIA. SH-1982, MIL-A-2550 AND MIL-P-70708 APPLY.
3. MATERIAL: SHEET, SAE OR MAST 1005-1010 STEEL,
CARBON, CAR RALL OR HOT RALL.
PER ASI'M A508, (ASI'M A306 OR A569). 130 + 13 GA (. 10) REF 2.81 ^{+.13} FULL SCALE \simeq 0.50 SECTION A-A SCALE 1/2 BS HOLES . 10 . 10 . 10 APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED. DISTRIBUTION STATEMENT A. 194 75



APPROVED SHEET 1 OF 1 POST SUPPORT PLATE ACV00307 ACTIVITY

U.S. ARNY

INDISTRIAL OFFENTIONS COMMODEFENTS AND SCHOOL

SAVANNA, ILLINOIS 61074-9639 YY-MM-DD DATE PART NO ACVOO307 SCALE 1/1 UNIT WI PRODUCT BASELINE EAR @#@### YY-MM-DD **FEVISION** DESIGN ACTIVITY S17E CAGE CODE C 28620 DESCRIPTION DAIRE, LOCISTICS BACINGSHING OFFICE APPROVED BY OFEEN OF COMMODIG. OHER, SUFFLY ENGINEERING DEV BJK TJM MICHELS DIS. APEN DE SOUR - 12 GA (.10) 96-06-05 1 SERITTED WESS OF WHITE SHELK DIMENSIONS WE HINDES. BREAK OF THRESTS WEST OF PRICES. FRACTIONS OF THE SHELL OF THE SHEL **.** 6.13 **HATBRIAL** ACVOD165 2.75 HYDRA ACVOD164 ROCKET NEXT ASSY USED ON APPLICATION 1. ANSI Y14.5M-1982, MIL-A-2550 AND MIL-P-70786 APPLY.
2. MATERIAL: SHEET, SAE OR ANSI 1005-1010 STEEL,
CARBON, COLD ROLL OR HOT ROLL,
PER ASTM A568, (ASTM A366 OR A569). 8.00 APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED. DISTRIBUTION STATEMENT A. NOTES:

- . Detail requirements for sufface preparation (cleming and pretifeation) to bare netal prior to printing and painting.
- 1.1 ALL SUFFACES SWALL BE THOROUGHLY CLEMED SUCH THAT THE BARE NETAL SUFFACES ARE FREE FIND OIL, GREAZE, DIRT, STALE, RIST, FOREIGN NATION AND LOOSE WELD SPATTER. THE CLEMING NETHOD SWALL BE THIN ACCORDINGE VITH ANY NETHOD IN TABLE IV OF RIL-10-171 OR ALS SPECIFIED IN PARACIACH 3.1 OF RIL-1-704, PARTICLUA CARE NIST BE TAKEN TO REPOYE NELD SLAG AND LOOSE WELD SPATTER FROM WELDS AND ALACENT APEXS.
- 1.2 INFEDIATELY AFTER CLEMING, ANY SOLVENTS OR NOISTURE SAUL RE CORPLETELY RENOWED.

 NESS CLEMA DRY SUFFICES SAULT. THEN HAVE A PRETREATHENT APPLIED IN ACCORDANCE
 NITH MILL-STD-171. FOR STEEL SUBSTRACES THE PRIFEARMENT TO USE IS SIMF PROSPAUTE,
 FINISH NO. 5.1.1, IRON PROSPAUTE, FINISH NO. 5.1.2 OR MASH PRINER, FINISH NO. 5.2.
- 1.3 INVEDIATELY PRIOR TO PRINTING, ALL SLIFACES WHICH HAVE BEEN CLEANED AND PRETREATED IN ACCORDANCE VITH PARACRAPH 1.1 AND 1.2 SHALL BE CHECKED FOR THOROUGH CLEANLINESS. ANY ACCUMULATION OF OIL, GREAKE, DUST, RESIDUES FROM THE CLEANING PROCESS ON ANY FOREIGN MITRIAL SHALL E COPPLETELY REPOVED. THE USE OF SOLVENTS HEETING THE REQUIREMENTS OF TRALE ITY, FINISH NO. 4.3 OF MILL-STI-171 IS ACCEPTABLE. THE COMPLETE DRYING OF ANY SOLVENTS ON MOTSTURE IS ESSENTIAL.
- DETAIL REQUIREMENTS FOR APPLICATION OF ANTI-COPPOSIVE PRINCE PAINT

٠i


- 2.1 PRIMER SYALL BE APPLIED ON ALL SUPFACES IN ACCORDANCE WITH MANJEACTURERS.
 INSTRUCTIONS AND PRANARANS 5.2.1 AND 5.2.2 OF INLESTOR-171 (EXCEPT INAT WEN
 ACELERATED DIVING IS BED.OFFED, ONEN TEMPERATURE IS NOT 10 EXCEED 200 DEPRES F).
 MIL.P-53022 OR MIL.P-53030 MAY BE USED ON EITHER FERROUS OR NON-FERROUS MATERIALS.
- 2.2 ONE COAT OF PRIMER SYNLL BE APPLIED AS PROPPLY AS POSSIBLE AFTEN THE SUFFACES HAVE BEEN PREPARED AND CLEANED BY THE AFOREHENTIONED PROCEDURES. THE PRIMER SYNLL BE COAT TO THE FOLICH IN ACCORDANCE WITH NIL.—C-53072. ALL BROXT PRIMERS SANLL BE PROPERLY ORIGIN BEFORE TOPCOATING, PRIMER DRY FILM THICONESS SANLL BE APPLIED TO ATTAIN THE 338 HOUR SALT SPAAY REQUIREMENT. RECONNENDED THICONESS PANCE IS .0010 TO .0035 INCHES SALT 60.0899 PM.).
- 3. DETAIL REQUIREMENTS FOR APPLICATION OF POLYUFETHME TOPCOAT PAINT.
- 3.1 TOPCOAT SWIL BE APPLIED ON EXTENTOR SUFFICES ONLY IN ACCORDANCE WITH MANUFACTURERS' INSTRICTIONS ON PANAGRAPIS 5.2.1 AND 5.2.2 OF MIL-STD-171. UNLESS OTHERISE SPECIFIED, THE TOPCOAT COLOR SWILL BE GREEN NO. 383 IN ACCROMACE WITH MIL-C-46168 OR MIL-C-53039.
- 3.2 TOPCOAT DRY FILM THICKNESS OF MIL-C-46168 AND MIL-C-53039 SWAL BE. CO18 TO .0035 INCHES, C.O457 TO .0899 MA) TOTAL APPLIED IN TWO COATS, THE SECOND COAT MAY BE APPLIED IN ACCORDANCE VITH MIL-C-53072 OR NAMEACIUMENS RECOMENDATIONS.
- 3.3 ALL PENORK SHALL BE IN ACCOPONACE WITH PARAGRAPH 3.5.1 OF HIL-C-53072.
- 3.4 ALTERNATE COATINGS HAY BE USED IF APPROVED BY THE CONTRACTING OFFICER.

	REVISION		
LTH	DESCRIPTION	DATE	APPROVED
V	CHANGE PAINT THICKNESS		
	REQUIREMENTS	87-09-17 ERNST	ERNST
8	PRODUCT BASELINE		
	ERR M8K9450	89-04-1d	F
	NOR M2T4200 92-07-20	•	
U	(ECP M3T4030 93-11-02)		SCHUL TZ
	(ECP M4T3005 94-06-02)	94-11-02	
0	NOR MST8003 95-05-09	65-06-07	SCHULTZ
ш	NOR MST3003 95-06-22	96-04-11	
	(ECP_MGR3004) 96-02-22		

- 4. CETAIL REQUIREMENTS FOR APPLICATION TO PREVIOUSLY PAINTED SUBSTRATES.
- 4.1 ALL PREVIOUSLY PAINTED SUFFACES MUST BE CLEAN AND FREE FROM RUST. WHERE RUST KITSTS, HOUNIGLA CLEANING IN ACCORDANCE WITH FINISH NO. 4.1 OF MILL-101-171 (WIRERBUSH IS ACCEPTABLE) SAULL BE PERFORMED UNTIL BRIGHT WE'LL IS SEPROSED. ONE COAL OF POLYMETHANE PAINT PER NILL-4-46168 OR NIL-C-53039 CAN BE APPLIED DIRECTLY PREPARATION EXCEPT CLEANING. IF THE MILLOS WITHOUT ANY ACCITIONAL SUFFACE PREPARATION EXCEPT CLEANING. IF THE SUFFACE IS BROCKEN DOWN TO THE SUBSTRATE, THAT AREA MUST BE CLEANED, PRETREATED, PRIVED AND TOPCOATED PER PARAGRAPH I LACOURS. THE LACOURS MUST BE REDOVED DOWN TO THE SUBSTRATE LACOURS. THE LACOURS MUST BE REDOVED DOWN TO THE SUBSTRATE CANTING IS APPLIED PER PARAGRAPHS I THROUGH 3.
- 4.2 WERE VEHICLE PARTS ARE SUPLIED TO THE MITE ORIGINAL EQUIPMENT WANTEACHER (OB) AREADY BANES.
 4.1 BY APRLYING DIRECTLY OVER THE EXISTING BANEL COATING. IF THE YEARD PARTS ARTIC JUST BANEL MILE OF THE OWNER THE OWNER THE OWNER OWNER THE OWNER OWNER THE OWNER THE OWNER OWNER THE OW
- 5. TESTING.
- 5.1 PALLETS MOJOR ADAPTERS FINISHED IN ACCORDANCE WITH PARAGRAPH 2.3, AND 4 AS APPLICABLE SHALL BE TESTED FOR PAINT ADHESTON USING ACTUAL PRODUCTION 1TEMS.
- 5.2 THE PRINES AND TOPCOAT SAUL BE ADJESTON TESTED IN ACCORDANCE WITH PARAGRAPH 4.2.7.2 OF TI-C-490.
- 5.3 THE PRINES AND TOPCOAT SAULL BE TESTED TAY PARAGRAPH 4.2.8 OF TT-C-490.
- 5.4 HIL-C-53072, PARAGRAPH 4.3.3.7 APPLIES

11.1	
DISTRIBUTION STATEMENT A.	APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED.

		٩	00-00-00	DESIGN ACTIVITY	
		SUMMER CREATER AND STATES		APPRAISENT	MILIONS AND CHEMICAL COMMAND
		Po. Braces on	CU YO 74 ITCEY	PA SENSE AN	DEFENSE APPLICATION CENTER AND SCHOOL
		FRACTION	מיוניאין אין ואין ואין		eria cioni di di
		SECTION S	T. J. MICHELS	CHENICAL AC	CHEMICAL AGENT RESISTANT COATING
		Mats .	OME. SPLY DEDUCED BY		(CARC) FINISHING REQUIREMENTS FOR
		MOKA	W. F. ERNST	HETAL PALLE	HETAL PALLETS AND/OR PALLET
			DAMP, LAKITHES BACKMENES OFFER	ADAPTERS	
			CACE. U.S. Are miles and care SIZE CACE CODE	SIZE CAGE CODE	
NEXT ASSY	USED ON			08820	AL 20000000
	10217		ישרוי הוחם, שתי	0~00~ 10	, , , , , , , , , , , , , , , , , , , ,
117	אדרוראוזמא		STALE NONE UNIT UT	SCALE NONE UNI	IT WI SHEET OF



NOTES:
1. FRAME: 'D'-RING, 0.38 STOCK DIA, 4140 STEEL,
5,000# SAFE WORKING LOAD, ULTIMATE STRENGTH
13,000# OH GREATER.
2. PLATING: IMMERSION ZINC FLAKE/CHRONATE DISPERSION
MIL-C-87115.

w.

SCHULTZ

94-11-02 5

ECP M913082-005 89-08-16 9
ECP M913087-005 89-09-19 9
NOR M214200 92-07-20
(ECP M014200 90-12-11)
(ECP M413005 94-06-02) 9
NOR M513003 95-06-22

APPROVED

OATE

REVISION

PRODUCT BASELINE


ERR M9T3051

90-09-24 DRETER 90-09-28 SCHULT

89-06-23

DIMENSIONS SHOWN ARE ENVELOPE DIMENSIONS
NECESSARY FOR THE RING TO MATE WITH THE RING
RETAINER AND TO PERFORM ITS INTENDED FUNCTION.
IDENTIFICATION OF THE SUGGESTED SOURCE(S) HEREON
IS NOT TO BE CONSTRUED AS A GUARANTEE OF PRESENT
OR CONTINUED AVAILABILITY AS A SOURCE OF SUPPLY FOR THE ITEMS)

SUGGESTED SOURCES OF SUPPLY	R DATA	NAME AND ADDRESS	U.S FORGECRAFT CORP. P.O. BOX 387 FT. SMITH, AR 72902	HELGESEN INDUSTRIES, INC. 7261 HIGHWAY 60 WEST HARTFORD, WI 53027
SUGGESTED SOL	SUPPLIER DATA	PART NUMBER	1070	204-115
		CAGE	16007	67480




SPECIFICATION CONTROL DRAWING

			1		
		OTHER TOP OF THE PARTY OF THE P	RQ-01-10	DESIGN ACTIVITY	A 10 A 10 A 1
		Suite CITACITY AND RITER		AMMANGENT	MENTAL AND CHEMICAL COMMAND
			E	DEFEN	DEFENSE APPLICATION CENTER AND SCHOOL
		MUSTING ST.			VANNA FLI PAOPE BLOCK OR 20
		FACTION	3		
		GEC Proc 1 13	VICTURE 1		
			WA K Out. But street as		
		IN IDEA.	TONGE A F ERNOT		LIFIING HING
			DAME, LAKISTICS DESIGNANG OFFICE		
			MANAGE BY DICENT OF COMMONDS.	300 ENG CODE	F
HEXT ASSY	USED ON		2000	28830	A COUCORD
200			יאר חווח די מווער	ב מחמפת	_
APPLI	APPLICATION		The state of the s	SCALE 1/1 UNIT WT	UNIT WI

7

DISTRIBUTION STATEMENT A.

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED.



ŀ	•								- PROJET BASE D	EXINITION ONE FROME TOWNSTAND THE BASELINE FOLIA COLOR - 23 COLOR	
PART NUMBER A	æ °	۾ ان	_ {	ш -	<u>ا</u> 8	= ¥	= 4		KOR H214200 (ECP H413005	02-20	T Ref
2 1.78	123	38.7.02	+	+-	1	+	Т.		(ECP HEREOGS)	03-16 03-18	
			APARTIE	APPLES TO PARIT-2 ONLY				2E NOTES 5 AND 6			
								MALIX should say	89-03-13 GE164 ACTIVITY	ACTIVITY TO SEE A SECTION OF THE COMMENT TO SEE A SECTION OF THE SEC	
								11	21	LIFTING RING	,
DISTRIBUTION STATEMENT A.								 	CARC RUB CARCALLES STEEL OF THE	RETAINER URE 1 COSTON	
DISTRIBUTION IS UN INITED.								NET ASS WIED BY	JOHN L. BYRD, JR. B 286	28628 AL 200000806	

APPENDIX 60

UNITIZATION PROCEDURES FOR BOXED AMMUNITION AND COMPONENTS PACKED IN CYLINDRICAL METAL OR PLASTIC CONTAINERS ON 4-WAY ENTRY METAL PALLETS

2.75" HYDRA ROCKET, PACKED 4 PER PA150 CYLINDRICAL METAL CONTAINER, UNITIZED 12 PER 78.50" X 29.31" SPECIAL METAL PALLET; APPROX CONTAINER SIZE 78.50" L X 9.25 W X 9.25" H

NOTICE: THIS APPENDIX CANNOT STAND ALONE BUT MUST BE USED IN CONJUNCTION WITH THE BASIC UNITIZATION PROCEDURES DRAWING 19-48-4231-20PM1006.

DISTRIBUTION STATEMENT A.

APPROVED FOR PUBLIC RELEASE;
DISTRIBUTION IS UNLIMITED.

ARMY MATERIEL COMMAND DRAWING U.S. DRAFTSMAN APPROVED, U.S. ARMY INDUSTRIAL OPERATIONS BETTY J. KUNDERT COMMAND ENGINEER SANDRA M. SCHULTZ SUPPLY ENGINEERING TRANSPORTATION ENGINEERING VALIDATION ENGINEERING DIVISION DIVISION DIVIZION AMSTA-AR-ESK LMT-012MA APPROVED BY ORDER OF COMMANDING GENERAL, U.S. ARMY MATERIEL COMMAND ≰PRIL 1994 CLASS NOIZIVIO DRAWING FILE U.S. ARMY DEFENSE AMMUNITION CENTER AND SCHOOL REVISION'NO. MARCH 1996 4231/ 20PM 48 19 60 1006 SEE THE REVISION LISTING ON PAGE 2

DO NOT SCALE


	PALLI	ET UNIT D	ATA	
ITEMS INCL	.UOED	HAZARD AND DIV		ADDDOV
NZN	DO DIC	OD CLASS	COMP GROUP	APPROX WEIGHT LBS
1340- 01-379-7814 01-289-4719 01-379-6347 01-379-7780 01-379-6350 01-379-7797 01-379-7889	1463 1463 1464 1464	(04)1.2 (04)1.2 (09)1.2 (09)1.2 (04)1.2	ошшоо	2,239 2,239 2,239 2,239 2,239 2,239 2,239

HAZARD CLASSIFICATION DATA CONTAINED IN THE ABOVE CHART IS
FOR GUIDANCE AND INFORMATIONAL PURPOSES ONLY. VERIFICATION
OF THE SPECIFIED DATA SHOULD BE MADE BY CONSULTING THE MOST
RECENT JOINT HAZARD CLASSIFICATION SYSTEM LISTING OR OTHER
APPROVED LISTING(S).

REVISION

REVISION NO. 1, DATED MARCH 1996, CONSISTS OF:

- 1. ADDING ITEM BY NATIONAL STOCK NUMBER TO "PALLET UNIT DATA" CHART.
- 2. CHANGING GENERAL NOTE "H" ON PAGE 3.
- 3. CHANGES IN ACCORDANCE WITH ECP M5T3003.



PALLET UNIT

SEE GENERAL NOTE "B" AT RIGHT.

12 CONTAINERS OF 2.75 HYDRA ROCKETS (4 PER CONTAINER) AT 162 LBS DUNNAGE	

TOTAL WEIGHT - - - - - - - 2,239 LBS (APPROX)
CUBE - - - - - - - - - 57.3 CU FT (APPROX)

BILL OF MATER	IAL
METAL PALLET, 78.50" X 29.31" - 1	REGD110 LBS
TOP ASSEMBLY 1 BOTTOM ASSEMBLY 1	REQD 85 LBS
STEEL STRAPPING, 3/4" 41.00' STEEL STRAPPING, 1-1/4" - 49.00'	REOD 2.93 LBS REOD 7.00 LBS
SEAL FOR 3/4" STRAPPING 4 SEAL FOR 1-1/4" STRAPPING 4	REOD NIL

GENERAL NOTES

- A. THIS APPENDIX CANNOT STAND ALONE BUT MUST BE USED IN CONJUNCTION WITH THE BASIC UNITIZATION PROCEDURES DRAWING 19-48-4231-20PM1006. TO PRODUCE AN APPROVED UNIT LOAD, ALL PERTINENT PROCEDURES, SPECIFICATIONS AND CRITERIA SET FORTH WITHIN THE BASIC DRAWING WILL APPLY TO THE PROCEDURES DELINEATED IN THIS APPENDIX. ANY EXCEPTIONS TO THE BASIC PROCEDURES ARE SPECIFIED IN THIS APPENDIX.
- B. DIMENSIONS, CUBE AND WEIGHT OF A PALLET UNIT WILL VARY SLIGHTLY DEPENDING UPON THE ACTUAL DIMENSIONS OF THE CONTAINER AND THE WEIGHT OF THE SPECIFIC ITEM BEING INTITIFED.
- C. BUNDLING STRAPS MUST BE TENSIONED AND SEALED PRIOR TO THE APPLICATION OF THE UNITIZING STRAPS. BUNDLING STRAPS MUST ALSO BE INSTALLED AS CLOSE TO THE OUTER RINGS AS POSSIBLE, TO AVOID DAMAGE TO THE CONTAINER.
- D. ALTHOUGH THE CONTAINERS DEPICTED IN THE UNIT LOAD AT LEFT ARE CONSTRUCTED WITH INTERLOCKING DEVICES, THE INTERLOCKS WILL NOT FUNCTION PROPERLY UNLESS THE CONTAINERS ARE POSITIONED SO THAT THE "PINS" OF THE INTERLOCKS ARE FACING UPWARD. THIS ORIENTATION WILL AID IN THE PREVENTION OF CONTAINER MOVEMENT, BOTH LATERALLY AND LONGITUDINALLY, DURING SHIPMENT OF THE UNIT LOAD.
- E. THE FOLLOWING AMC DRAWINGS ARE APPLICABLE FOR OUTLOADING AND STORAGE OF THE ITEMS COVERED BY THIS APPENDIX.

CARLOADING - - - 19-48-4242/60-5PM1004
TRUCKLOADING - - 19-48-4243/60-11PM1004
STORAGE - - - 19-48-4250-1-2-3-4-14-22PM1004
END OPENING ISO
CONTAINER - - - 19-48-4245/60-15PM1009
MILVAN - - - - 19-48-4244/60-15PM1008
SIDE OPENING ISO
CONTAINER - - - 19-48-4272/60-15PM1016

- F. FOR METHOD OF SECURING A STRAP CUTTER TO THE PALLET UNIT, SEE AMC DRAWING 19-48-4127-20P1000.
- G. IF ITEMS COVERED HEREIN ARE UNITIZED PRIOR TO ISSUANCE OF THIS APPENDIX, THE CONTAINERS NEED NOT BE REUNITIZED SOLELY TO CONFORM TO THIS APPENDIX.
- H. FOR DETAILS OF THE PALLET AND PALLET ADAPTERS, SEE AMCCOM DRAWING ACVO0156, MIL-A-70788 AND MIL-P-70786.
- J. THE UNITIZATION PROCEDURES DEPICTED HEREIN MAY ALSO BE USED FOR UNITIZING 2.75" HYDRA ROCKETS WHEN IDENTIFIED BY DIFFERENT NATIONAL STOCK NUMBERS (NSN) THAN WHAT IS SHOWN ON PAGE 2, PROVICED THE CONTAINER PACK DOES NOT VARY FROM WHAT IS DELINEATED HEREIN. THE EXPLOSIVE CLASSIFICATION OF OTHER ITEMS MAY BE DIFFERENT THAN WHAT IS SHOWN.
- K. EMPTY OR REJECT PALSO CONTAINERS WILL BE USED AS FILLER CONTAINERS AS NECESSARY. FILLER CONTAINERS MUST BE INSTALLED IN THE MIDDLE OF THE TOP LAYER(S) OF CONTAINERS. IF FOUR FULL CONTAINERS ARE TO BE OMITTED. ONE FULL LAYER OF CONTAINERS WILL BE OMITTED. WHEN (REJECTED) FILLER CONTAINERS WILL BE OMITTED. CONTAINERS TO COMPLETE A LAYER ON A PALLET, THEY WILL BE MARKED AS SPECIFIED WITHIN MIL-STD-129-1, EXCEPT WHEN (EMPTY/REPAIRABLE) CONTAINERS ARE USED IN PLACE OF OMITTED CONTAINERS TO COMPLETE A LAYER ON A PALLET; THE WORD "EMPTY" WILL BE STENCILED IN ORANGE ON THE EMPTY CONTAINER IN 1-INCH SIZE LETTERS. THE WORD "EMPTY" WILL BE STENCILED IN ORANGE ON THE EMPTY CONTAINER WITH THE WORDS PAINTED ALONG THE CONTAINER WITH THE WORDS PAINTED ALONG THE CIRCUMFERENCE, 180 DEGREES APART, AND THREE TIMES ON THE BODY PORTION OF THE CONTAINER WITH THE WORDS PAINTED LENGTHWISE ON THE CONTAINER WITH THE WORDS PAINTED ALONG THE
- L. FOR DETAILS OF THE PA150 CONTAINER SEE PICATINNY DRAWING 12937855-2.

